

**Technical Specs - Marey outdoor units**

Supplier Model No.	Marey 30 liters outdoor - Natural and Propane Gas	Marey 26 liters outdoor - Natural and Propane Gas	Marey 22 liters outdoor - Natural and Propane Gas
Capacity	30 liters	26 liters	22 liters
Current Certificate	CSA	CSA	CSA
Forced Exhaust Type	Outdoor	Outdoor	Outdoor
Copper Heat Exchanger	Oxygen Free Copper	Oxygen Free Copper	Oxygen Free Copper
Nominal Power / Rated Heat Input (BTU)	199,000	180,000	150,000
Rated Hot Water Production Capacity (25K)	30L/min-8Gal	26L/min-7Gal	22L/min-6Gal
Temperature Control Range (°F)	100-140	100-140	100-140
Ignition Mode	Pulse Ignition	Pulse Ignition	Pulse Ignition
Suitable Water Pressure (PSI)	3.0-145PSI	3.0-145PSI	3.0-145PSI
Solenoid Valves	24v	24v	24v
Safety Devices	<ol style="list-style-type: none"> <li>1. Flame failure protection</li> <li>2. Over-high water pressure safety device</li> <li>3. Anti-dry combustion protection</li> <li>4. Protection for fan failure</li> <li>5. Protection for over-loaded electric system</li> <li>6. Over-high wind pressure safety device</li> <li>7. Over-temperature protection</li> <li>8. Anti-freezing protection</li> </ol>	<ol style="list-style-type: none"> <li>1. Flame failure protection</li> <li>2. Over-high water pressure safety device</li> <li>3. Anti-dry combustion protection</li> <li>4. Protection for fan failure</li> <li>5. Protection for over-loaded electric system</li> <li>6. Over-high wind pressure safety device</li> <li>7. Over-temperature protection</li> <li>8. Anti-freezing protection</li> </ol>	<ol style="list-style-type: none"> <li>1. Flame failure protection</li> <li>2. Over-high water pressure safety device</li> <li>3. Anti-dry combustion protection</li> <li>4. Protection for fan failure</li> <li>5. Protection for over-loaded electric system</li> <li>6. Over-high wind pressure safety device</li> <li>7. Over-temperature protection</li> <li>8. Anti-freezing protection</li> </ol>
Panel	Steel with Painting	Steel with Painting	Steel with Painting
Gas Inlet	NPT G3/4"	NPT G3/4"	NPT G3/4"

Cold Inlet Water	NPT G3/4"	NPT G3/4"	NPT G3/4"
Hot Outlet Water	NPT G3/4"	NPT G3/4"	NPT G3/4"
Burner (Row)	20	23	23
Rated Voltage / Freq	110V Automatic Exchange	110V to 240V Automatic Exchange	110V Automatic Exchange
Electrical Power Rate (W)	52	54	54
Energy Factor	0.84	0.84	0.84
N.Weight (LBS)	47,39 lbs	45.19	45.19
G.Weight (LBS)	52,91 lbs	48.50	48.50
Product dimensions (H x W x D)	21.35" x 14.34" x 9.25"	22 3/7" x 15 1/2" x 7.31"	22 3/7" x 15 1/2" x 7.31"
Packaging dimensions (H x W x D)	27.35" x 17.45" x 13"	27.25" x 19.12" x 10"	27.25" x 19.12" x 10"