




# TEMPERATURE MAP

## CHOOSE YOUR MAREY TANKLESS WATER HEATER BASED ON YOUR CLIMATE

To find the best model for you and identify the unit's capacity match your location on the map with the table on the right.



ELECTRIC UNITS				GAS UNITS		
POINTS OF USE	GPM	PRODUCT	INLET °F	PRODUCT	GPM	POINTS OF USE
1	4.0	ECO180	35°F	GA10 FNG/FLP	3.4	1
				GA14 NG/LP	4.6	2
				GA20 NG/LP	6.87	3
				GA24 NG/LP	8.34	4
2	1.6	ECO110	45°F	GA5 FNG/FLP	1.4	1
3	2.5	ECO150		GA10 FNG/FLP	2.6	2
4	3.0	ECO180		GA14 NG/LP	3.6	3
				GA20 NG/LP	5.7	4
				GA24 NG/LP	7.1	5
3	1.5	PP220	55°F	GA5 FNG/FLP	1.2	1
4	1.5	ECO110		GA10 FNG/FLP	2.1	2
5	1.7	ECO150		GA14 NG/LP	2.9	3
6	2.5	ECO180		GA20 NG/LP	4.5	4
				GA24 NG/LP	5.9	5
4	1.0	PP220	65°F	GA5 FNG/FLP	1.0	1
5	1.25	ECO110		GA10 FNG/FLP	1.8	2
6	1.5	ECO150		GA14 NG/LP	2.5	3
7	2.0	ECO180		GA20 NG/LP	3.8	4
				GA24 NG/LP	5.5	5

 SHOWER WORKING ON 1.5 GPM     
  HAND SINK FAUCET WORKING ON 1.0 GPM

RESULTS BASED ON AN OUTLET TEMPERATURE OF 105°F

### TYPICAL GPM REQUIREMENTS FOR VARIOUS FIXTURES

Hand Washing Sink	0.5 - 1.0 GPM	Shower	1.5 - 2.0 GPM
Washing Machine	1.0 - 1.5 GPM	Utility Faucet	1.5 - 2.0 GPM
Residential Dishwasher	1.0 - 2.0 GPM	Bathtub	4.0 - 5.0 GPM
Residential Kitchen Sink	1.5 - 2.0 GPM		

### PROPER SIZING EXAMPLE

Bathroom Lavatory Sink	1.0 GPM
Standard Shower	2.0 GPM

### TOTAL GPM DEMAND

Running at the same time 3.0 GPM